

Dryflow Slimforce

ITEM KEY	ITEM DESCRIPTION	ITEM QTY	NOTES
A	Hand Dryer Unit Complete	1	Stainless Steel 304 Cover & Cabinet
B	Owner Manual (OM - this booklet)	1	
C	Mounting Template (MT)	1	
D	Wall Anchors, Expansion	4	φ8x38MM (5/16" Dia.x 1-1/2"), for#10
E	Self-threading Phillips PH Screws	4	M5x36MM (No.10 AB x 1-3/16")
F	Flat Washer	4	F1 For M5(No.10 AB)Phillips PH Screws
G	Hex Key (for cover screws)	1	For 4MM(5/32") hex socket FH Screws

When size matters, their value's worth every penny



low traffic




SPECIFICATION

Voltage:	220V-240V 50/60Hz,4A/1000W
Stand-by Power:	Less than 2.0W
Air Temperature:	40°C (104°F)(Distance from nozzle=100MM(4"),Room Temp.=25°C (77°F))
Air Velocity:	100M/S(328 FT/S) / 360KM/H(224MPH)
Air Flow:	130M ³ /H(76.5CFM)
Drying Time:	10-12 Seconds
Timing Protection:	Forced Hold-On 60 Seconds auto shut-off
Timing Duration:	Auto Shut-Off ≤3 Seconds after last sensor read
Sensor Range:	5-15CM(2" ~ 5.7/8"), Owner Adjustable
Fuse Protection:	1kW max inrush current, 250V, 6A(230V)
Protection Level:	IP23
Electric Isolation:	CLASS I (Metal cover)
Brush Motor:	30000RPM, 600W(0.8HP)
Noise (at 1M):	74dB
Weight :	2.5KG(5.5lb)/Net Weight / 3.0KG(6.6lb)/Shipping Weight

ONLY to be used on same voltage as product rated label marked.

- Blue LED light shines on the hands when activated
- Air filter included as standard
- Very energy-efficient
- Minimal running cost
- Very slim and compact
- Robust & durable

For life.
FREE REPAIRS FOR LIFE



Dries possible per £1	2,500
Electrical Supply Voltage	220-240 V
Electrical Supply Frequency	50/60 Hz
Expected Motor Life	800 Hours
Rated Power	0.6 kW - 1 kW (Internal on / off heater switch)
Approx. Watt-Hours per Dry	2 - 2.78 Wh
Heater Element Power	0.4 kW
Operating Sound Level	74 dB
Motor Speed	30,000 RPM
Air Speed	224 MPH

Air Speed	224 MPH
Operating Temperature Range	At ambient temp (20°C) - 40°C
Motor Cut off Time	60 seconds
Motor Class	Class I
Materials	Stainless steel
Weight	2.5 kg
Finishes Available & Codes	Brushed satin (DFLIF02)
IP Rating	IP23
Cable Entry Point	Rear, with access available from bottom
Certifications and Awards	CE